



TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark
TSE veya/or  veya/or T S E

BELGE NUMARASI
REFERENCE NUMBER OF LICENCE

022438-TSE-01/05

BELGENİN İLK VERİLİŞ TARİHİ
DATE OF FIRST ISSUE OF LICENCE

02.02.2007

BELGENİN SON GEÇERLİLİK TARİHİ
LICENCE VALID UNTIL

09.07.2026

BELGE SAHİBİ KURULUŞUN ADI
NAME OF THE LICENCE HOLDER

TEKNOPANEL ÇATI VE CEPHE PANELLERİ ÜRETİM
SANAYİ VE TİCARET ANONİM ŞİRKETİ

BELGE SAHİBİ KURULUŞUN ADRESİ
ADDRESS OF THE LICENCE HOLDER

ORGANİZE SAN.BÖLGE 7.CADDE NO:10 AKDENİZ
MERSİN/TÜRKİYE

ÜRETİM YERİ ADI
NAME OF THE MANUFACTURING PLACE

TEKNOPANEL ÇATI VE CEPHE PANELLERİ ÜRETİM SANAYİ VE
TİCARET ANONİM ŞİRKETİ

ÜRETİM YERİ ADRESİ
ADDRESS OF THE MANUFACTURING PLACE

ORGANİZE SAN.BÖLGE 7.CADDE NO:10 AKDENİZ MERSİN /
TÜRKİYE

İPTAL EDİLEN BELGE NUMARASI (Varsa)
INDICATION OF SUPERSEDED LICENCE (if any)

022438-TSE-01/04

TESCİLLİ TİCARİ MARKASI
REGISTERED TRADE MARK

teknopanel teknopor şekil

İLGİLİ TÜRK STANDARDI
RELATED TURKISH STANDARD

TS EN 13163:2012+A2 / 09.01.2017

BELGE KAPSAMI
SCOPE OF LICENCE

Factory made expanded polystyrene (EPS) foam product used for thermal insulating of buildings. Surface Property:
Flat Coated Surface Type: Uncoated Situation of Fitted Each Other: Non-fitted

Types:

1-EPS 80 Min, Classification of Fire: E – Classification of Dimensions: - Tolerance of Length: L(2) – Tolerance of Width: W(2) – Tolerance of Thickness: T(2) – Tolerance of Deviation of Squareness: Sb(5) – Tolerance of Flatness: P(3) – EPS80; Coefficient of Thermal Conductivity (λ): 0.038 W/mK – Bending Strength: BS150 – Compressive Stress at 10% Deformation: CS(10)80 - Dimensional Stability Under Constant Normal Laboratory Conditions: DS(N)5 – Tensile Strength Perpendicular To Faces: TR150 - Dimensional Stability Under Specified Temperature And Humidity Conditions: DS(70,)1 – This product cannot be used for implementations needed compressive creep.

2-EPS 80 (Graphite) Min, Classification of Fire: E – Classification of Dimensions: - Tolerance of Length: L(2) – Tolerance of Width: W(2) – Tolerance of Thickness: T(2) – Tolerance of Deviation of Squareness: Sb(5) – Tolerance of Flatness: P(3) – EPS80; Coefficient of Thermal Conductivity (λ): 0.031 W/mK – Bending Strength: BS120 –

e-imzalı/e-signed

23.06.2025

On Behalf Of The Head Of Certification Center
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS
SECTOR

*This certificate also shows that the production place of the certified product meets the requirements of Institute.

*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE * Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA * Telephone: 0312 416 63 79* Fax: 0312-416 66 17

*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail

:bmb@tse.org.tr , web : www.tse.org.tr





TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS



(022438-TSE-01/05nolu belge devamı) : TEKNOPANEL ÇATI VE CEPHE PANELLERİ ÜRETİM SANAYİ VE TİCARET ANONİM ŞİRKETİ
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 13163:2012+A2 / 09.01.2017

Compressive Stress at 10% Deformation: CS(10)60 - Dimensional Stability Under Constant Normal Laboratory Conditions: DS(N)5 - Tensile Strength Perpendicular To Faces: TR100 - Dimensional Stability Under Specified Temperature And Humidity Conditions: DS(70,)1 - This product cannot be used for implementations needed compressive creep.

3-EPS 100 Min, Classification of Fire: E - Classification of Dimensions: - Tolerance of Length: L(2) - Tolerance of Width: W(2) - Tolerance of Thickness: T(2) - Tolerance of Deviation of Squareness: Sb(5) - Tolerance of Flatness: P(3) - EPS100; Coefficient of Thermal Conductivity (λ): 0.035 W/mK - Bending Strength: BS200 - Compressive Stress at 10% Deformation: CS(10)100 - Dimensional Stability Under Constant Normal Laboratory Conditions: DS (N)5 - Tensile Strength Perpendicular To Faces: TR200 - Dimensional Stability Under Specified Temperature And Humidity Conditions: DS(70,)1 - This product cannot be used for implementations needed compressive creep.

4-EPS 120 Min, Classification of Fire: E - Classification of Dimensions: - Tolerance of Length: L(2) - Tolerance of Width: W(2) - Tolerance of Thickness: T(2) - Tolerance of Deviation of Squareness: Sb(5) - Tolerance of Flatness: P(3) - EPS120; Coefficient of Thermal Conductivity (λ): 0.035 W/mK - Bending Strength: BS200 - Compressive Stress at 10% Deformation: CS(10)120 - Dimensional Stability Under Constant Normal Laboratory Conditions: DS (N)5 - Tensile Strength Perpendicular To Faces: TR200 - Dimensional Stability Under Specified Temperature And Humidity Conditions: DS(70,)1 - This product cannot be used for implementations needed compressive creep.

5-EPS 150 Min, Classification of Fire: E - Classification of Dimensions: - Tolerance of Length: L(2) - Tolerance of Width: W(2) - Tolerance of Thickness: T(2) - Tolerance of Deviation of Squareness: Sb(5) - Tolerance of Flatness: P(3) - EPS150; Coefficient of Thermal Conductivity (λ): 0.034 W/mK - Bending Strength: BS250 - Compressive Stress at 10% Deformation: CS(10)150 - Dimensional Stability Under Constant Normal Laboratory Conditions: DS (N)5 - Tensile Strength Perpendicular To Faces: TR200 - Dimensional Stability Under Specified Temperature And Humidity Conditions: DS(70,)1 - This product cannot be used for implementations needed compressive creep.

e-imzalı/e-signed

23.06.2025

On Behalf Of The Head Of Certification Center
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS
SECTOR

*This certificate also shows that the production place of the certified product meets the requirements of Institute.

*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE * Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA * Telephone: 0312 416 63 79* Fax: 0312-416 66 17

*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA - Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

